

# NG1000 Weather Radio

PHONE +1.902.823.2233

FAX +1.902.823.3183

info@nautel.com

www.nautel.com

## GENERAL

# **Transmitter Type**

Narrowband FM

## **RF Output Power**

200-1000 W continuously adjustable, VSWR 3:1 maximum with auto foldback at higher reflected power

## **RF Output Connection**

Type 7/16 DIN, female

## **RF Output Impedance**

50 ohms unbalanced

# **RF Frequency Range**

162.400 MHz to 162.550 MHz in 25 kHz steps

## **Spurious and Harmonic**

Less than -73 dBc (TIA/EIA-603)

## **Output Bandpass Filtering**

Bandpass cavity, I.L < 0.5 dB, > 10 dB attenuation at Fo +/-1 MHz

## **Remote Diagnostics**

Available through a modem, voice grade line or LAN with RS232 DTE, RJ11 DCE, USB, and Ethernet

#### **Local Visual Indicators**

All operating parameters and status of all remotely sensed parameters/conditions

## AC INPUT

#### **AC Input Range**

1 Phase 187 to 264 Vac 47 to 63 Hz

## **Power Consumption**

Less than 2500 VA at 1000 W output

# AUDIO SPECIFICATIONS

Main Audio Input 600 Ohm balanced

## **Main Audio Input Level Deviation**

-20 dBm to +5 dBm for +/- 5 kHz deviation

## **Audio Response**

200 Hz to 5 kHz, 6 dB/octave pre-emphasis

# **Sub Audible Input**

600 Ohm balanced

#### **Sub Audible Input Level Deviation**

0 dBm, 0 Hz to 200 Hz for +/- 1 kHz deviation, adjustable gain +/- 6 dB

## **Frequency Stability**

Better than +/- 0.0005% from -30° C to +50° C

## **Audio Distortion**

Less than 1%

#### FM Hum and Noise

Better than -40 dB

#### **AM Noise**

Better than -34 dB (TIA/EIA - 603)

## ENVIRONMENTAL

## **Temperature Range**

-30° C to +50° C

## **Humidity Range**

10% to 95% non-condensing and in salt laden air

#### Altitude

0 m to 4572 m (0 ft to 15,000 ft)

## Cooling

Forced filtered air input with duct flange output

Filters replaceable without interruption of transmitter

# PHYSICAL

#### **Dimensions**

**D**ual system:

122.9 cm H x 58.4 cm W x 81 cm D (48.4" H x 23" W x 31.9" D)

With cavity filter and dummy load:

122.9 cm H x 89.1 cm W x 81 cm D (48.4" H x 35.1" W x 31.9" D)

Transmitter only:

W = 48.3 cm (19") - Standard 19" rack

H = 17.8 cm (7") - 4RU

D = 60.2 cm (23.7") - Including output connector

## Weight

Dual system + cavity filter and dummy load: 186.4 kg (410 lbs)

1250 W transmitter: 22.7kg (50 lbs)